

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8420)

Set a granite stone 18x14x6", 12" in the ground for ¼ sec. cor. mkd. ¼ on North face, from which
A fir, 36" dia., bears N.8°E., 24 lks., mkd: ¼ S29 BT.
A fir, 30" dia., bears S.42°W., 17 lks., mkd: ¼ S32 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-29

Found - 18x14x6" Stone, firmly set, mkd: "¼" on north face. Orig. 36", now 44" D.Fir, N.8°E., 15.8 ft., shows good scar.
Orig. 30" D.Fir, now rotted stump, S.42°W. 11.2 ft., opened for scribing.
Set brass Cap at Cor. mkd: County Surveyors T32S R3W
Office ¼ S 29 Doug. Co.
1969 S 32 Jack. Co.
New BT - 6" D.Fir S.50°E. 25.4 ft., mkd: "¼ S32 CS BT"