

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8444)

-----  
Set a granite stone 15x8x5", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
A fir, 12" dia., bears N.33°E., 4 lks., mkd: ¼ S20 BT.  
A fir, 18" dia., bears S.57°W., 29 lks., mkd: ¼ S29 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-22

-----  
Found - 15x8x5" stone, firmly set, mkd: "¼" on north face. Orig. 18", now 24" D.Fir, S.57°W., 19.1 ft. shows scar.

No trace of NE BT, logged unit.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T32S R3W  
OFFICE ¼ S 20  
1969 S 29

New BT - 7" Yew N.3°W., 39.7 ft. mkd: "¼ S20 CS BT"

Reblazed & rescribed -

24" D.Fir S.57°W., 19.1 ft. mkd: "¼ S29 CS BT"

Kris DeGroot - For: USFS - June 2007 - C.S. 65/60-49

-----  
Found - A 1½" dia. Galvanized iron post, firmly set, projected 16" above the ground with a 2½" dia. brass cap (properly) stamped. 1969

From which an original bearing tree:

A 31" D.Fir snag bears S.57°W., 19.1 ft. with a healed blaze.

And bearing trees by Powell in 1969:

A 11" Yew bears N.3°W., 39.7 ft. with scribe marks "0 CS BT" visible on a partially healed blaze. (Rec. N.3°W.)

New - A 9" D.Fir bears S.54°E. 12.3 ft scribed "¼ S29 BT"

Note - All new BTs have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown and distances are measured to an aluminum nail in the root crown at the side and center of the tree. All bearing trees have a 6" red band painted around the tree and the blazed face painted red and Bearing Tree and USFS Land Survey Monument sign nailed to the tree.