

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 20

Alias	Description

Malcolm Clark, Chickering Green/Empire INC - For: USFS - 3/21/1980 - M82-68 & C.S. File 58/227(N)

Set - Aluminum cap by proportion marked: T32S R3W C¼ S20 RLS 601 1980.
New - 8" Hemlock, S.76°10'W., 44.0 ft.
14" Hemlock, N.35°10'E., 49.4 ft.
Both scribed "T32S R3W C¼ S20 BT"

Kris DeGroot - 8/2007 - For: USFS - C.S. 65/60-50

Found - A 2½" dia. aluminum post, firmly set, projecting 8" above the ground with a 2½" dia. aluminum cap (properly) stamped. 1980
From which bearing trees by Clark in 1980:
A 13" Hemlock bears S.76°10'W., 44.0 ft. with a healed double blaze. (Rec. S.76°10'W.)
A 14" Hemlock snag with broken top bears N.35°10'W., 49.4 ft. with scribe marks "T32S R3W C ¼ S20 BT" visible on a partially healed double blaze. (Rec. N.35°10'W.)
New - A 9" D.Fir bears S.66°E. 9.9 ft scribed "C ¼ S20BT"
Note - All new BTs have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown and distances are measured to an aluminum nail in the root crown at the side and center of the tree. All bearing trees have a 6" red band painted around the tree and the blazed face painted red and Bearing Tree and USFS Land Survey Monument sign nailed to the tree.