

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8373)

Set ¼ sec. post, from which
 A laurel, 12" dia., bears North, 7 lks.
 A Pine, 24" dia., bears S.2°W., 70 lks.

Douglas Co. Surveyors Office - John M. Powell - 8/20/1969 - C.S. File 54/91

Reported as not found.
Fd. E-W brushed line near approx. ¼ cor. BTs pine & laurel in general area of cor., fd only 1 pine standing which was far too big. I cut into this tree for ring count. Area has been burnt at one time. I find no down pines.

Malcolm Clark - For: USFS - April 1980 - M83-55 & C.S. File 58/227(n)

Set - Alum. cap by proportion, stamped: T32S R3W ¼ S8 S17 1980 RLS 601.
 13" D.Fir bears N.06½°W., 63.5 ft. scribed "T32S R3W ¼ S8 BT"
 16" D.Fir bears S.72°W., 33.6 ft. scribed "T32S R3W ¼ S17 BT"

Fd. Ok by G. Lang - 7/1995 - M123-79