

PRIMARY CORNER DESCRIPTION CC Secs. 16 & 17 only, south

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Glenn Baughman - For: USFS - Nov. 1979 - C.S. File 58/176-19

Found - 1" Iron pipe, firmly set, 12" above ground with 2½" brass cap mkd: "County Surveyors Office T32S R3W S16 S17 S20 1969".

From which original bearing trees: -

A 10" W.Fir snag, scribe marks S17 T32S R3" visible bears N.40°W., 4.6 ft. (Record 2.6 ft.)

A 8" W.Fir, scribe mark "2" visible on an open blaze, bears N.43°E., 12.5 ft.

and bearing tree mkd by Powell

30" D.Fir, with partially healed blaze, bears S.71°E., 6.8 ft.

Also fd. a 15x8x6 Serpentine stone with 4 notches on the East edge set adjacent to and on the south side of the brass cap.

New BT - A 16" D. Fir, bears N.68°W., 42.1 ft., marked "T32S R3W S17 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.

Leonard Herzstein, USFS - Aug/Sept 2007 - M154-54 & C.S. 65/61-12

Found - A 1¼" outside dia iron pipe, firmly set, projecting 14" above ground, with a 2½" dia. brass cap (properly) marked as shown. The cap is twisted 45° clockwise.

From which the remains of the orig bearing trees:

32" D.Fir, bears S.70°E., 6.6 ft, with healed double blaze. Marks on tree were destroyed by Mensch in 1913 & the tree was rescribed by Powell in 1969 (rec. 1969, S.71°E, 6.8 ft).

8" decayed W.Fir snag, bears N.40°W., 4.6 ft, with partially healed double blaze (rec. 20", 4 links = 2.64 ft)

And bearing tree marked by Mensch in 1913:

10" W.Fir, bears N.43°E., 12.5 ft, with healed double blaze (rec. 19 links = 12.54 ft).

And bearing tree marked by Baughman in 1969:

18" D.Fir, bears N.68°W., 42.1 ft. with healed double blaze.