

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8419)

-----

Set a sandstone 18x10x8", 12" in the ground for cor. of secs. 28, 29, 32, & 33 mkd with 1 notch on south & 4 notch(es) on East edges, from which

    A fir, 40" dia. bears N.3°E., 73 lks. mkd: T32S R3W S28 BT

    A hemlock, 6" dia., bears S.81°E., 35 lks., mkd: T32S R3W S33 BT.

    A fir, 40" dia. bears S.76°W., 57 lks mkd: T32S R3W S32 BT

    A fir, 60" dia. bears N.47°W., 13 lks mkd: T32S R3W S29 BT

---

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-25

-----

Found - 18x10x8", stone mkd: 4 notches on East and 1 on South, firmly set

    40", now 44" D.Fir, N.3°E., 48.2 ft., shows good scar.

    6", now 16" Hemlock, S.81°E., 23.1 ft., shows good scar.

    40", now 46" D.Fir, S.76°W., 37.6 ft., shows good scar.

    60" D.Fir, now 68" N.47°W., 8.6 ft.

Set - Brass cap at corner mkd:

            County Surveyor      T32S   R3W

                                  Office      S 29|S 28 Doug. Co.

                                  1969      S 32|S 33 Jack. Co.

New BTs- 10" Cedar N.60°E., 17.0 ft. Mkd. T32S R3W S28 CS BT

          14" Hemlock S.22°W., 14.0 ft Mkd: T32S R3W S32 CS BT

---

Jackson Co. Surveyors Office - Edward McGinty, County Surveyor - R. Frost, Tech. - S. Beecher, Tech. - Oct. 6, 1988 - C.S. File 63/82-12

-----

Found - Projecting 12", the 1" dia. galv. iron pipe with 2½" dia. (Douglas Co.) brass cap (properly) mkd.:

    The original 18x8x6 ins. (serpentine) stone mkd. with "X" on top and 1 and 4 grooves on adjacent sides, is found alongside corner.

    OBTs mkd. by F Mensch in 1913 fd:

        The center of partial stump remains of a tipped over (large) fir, brs. N.6°E., 48.18 ft Rec; N.3°E. Hemlock, 16" dia. with healed blazes, brs. S.80°E., 21.87 ft. to center of tree, at lower blaze. Rec; S.81°E., 23.10 ft.

continued next page

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Sawed Fir stump, 48" dia., with healed blazes, brs. S.76°W., 38.07 ft to center. Record; 37.62 ft.  
Sawed Fir stump, 60" dia. with healed upper blaze, brs. N.47°W., 8.65 ft to center. Record; 8.58 ft.  
Bearing trees mkd. by Douglas County in 1969, fd. at record location:  
Cedar, 13" dia. with scribe mks. visible in partly exposed face, brs. N.60°E., 17.0 ft. to center.  
Hemlock, 15" dia. with scribe mks. visible in partly healed blaze, brs. S.22°W., 14.0 ft. to center.  
New - D.Fir, 11" dia., brs. N.20°W., 20.60 ft. to center of tree at lower blaze. "CS" "BT"  
Corner lies on East slope, about 800 ft. South of location marker on 12" dia. fir, located alongside road, c. N.75°E.