

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8438)

-----  
Set a granite stone 20x8x6", 15" in the ground for cor. of secs. 20, 21, 28, & 29 mkd with 2 notches on S & 4 notches on E edges, from which  
A fir, 30" dia. bears N.12°E., 40 lks mkd: T32S R3W S21 BT  
A madrona, 12" dia., bears S.53°E., 27 lks., mkd: T32S R3W S28 BT.  
A chinquapin, 16" dia., bears S.58°W., 50 lks., mkd: T32S R3W S29 BT.  
A S.Pine, 40" dia., bears N.5°W., 69 lks., mkd: T32S R3W S20 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - 7/17/1969 - C.S. File 54/91-21

-----  
Found - Possible corner stone but no marks.  
Orig. 16" Chinquapin, now down S.58°W., 33.0 ft., scribe visible.  
No trace of other BTs or stone because of road work.  
Set brass cap at cor. mkd: COUNTY SURVEYORS T32S R3W  
OFFICE S 20 | S 21  
1969 S 29 | S 28  
New BTs- 40" D.Fir N.52°E., 104.8 ft. mkd: T32S R3W S21 CS BT  
12" D.Fir N.55°W. 21.9 ft. mkd: T32S R3W S20 CS BT.  
16" D.Fir S.39°W. 41.7 ft. mkd: T32S R3W S29 CS BT.  
21" D.Fir S.55°E. 34.2 ft. mkd: T32S R3W S28 CS BT.  
This corner lies 40 ft. south of logging road.

Malcolm Clark, Chickering Green/Empire INC - For: USFS - 3/21/1980 - M82-68 & C.S. File 58/227(N)

-----  
Found - 1969 County Brass cap  
44" D.Fir stump, N.52°05'E., 105.4 ft.  
Rotten stump, S.54°10'E., 33.4 ft.  
14" stump, S.39°05'W., 41.4 ft.  
12" D.Fir, N.54°15'W., 22.1 ft.  
New BTs- 22" D.Fir, N.78°20'E., 154.2 ft. scribed "T32S R3W S21 BT"  
12" D.Fir, S.48°20'E., 259.5 ft. scribed "T32S R3W S28 BT"  
16" D. Fir, S.16°55'W., 95.7 ft. scribed "T32S R3W S29 BT".