

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 17

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8370)

Set ¼ sec. post, from which
A Laurel, 5" dia., bears East 5 lks.
A Fir, 24" dia., bears S.45°W., 4 lks.

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8407-08)

Page 8407
North between Secs. 16 & 17. At 40.00 chs after careful search, I find no trace of the ¼ sec. cor.
Page 8408
Apportioned distance.
Set a granite stone 15x14x6" 10" in the ground for ¼ sec. cor. mkd ¼ on West face, from which
A fir, 14" dia., bears N.52°E., 36 lks., mkd: ¼ S16 BT.
A fir, 36" dia., bears N.59°W., 34 lks., mkd: ¼ S17 BT.
I again make search for old ¼ sec. cor. but can find no trace of same.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Sept. 1969 - C.S. File 54/91-81

Found - 14" now 26" D.Fir N.52°E., 23.8 ft. shows good scar.
36" now 39" D.Fir N.59°W., 22.4 ft. shows good scar.
15x14x6" stone, firmly in ground, mkd: "¼" on west face.
Set brass cap at cor. mkd: COUNTY SURVEYORS T32S R3W
OFFICE 1969 ¼ S 17|S 16
All BTs OK & tagged.