

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8369)

Set post, cor. to secs. 8, 9, 16, & 17, from which
A pine, 12" dia., bears N.10°E., 72 lks.
A pine, 12" dia., bears S.32°E., 160 lks.
A pine, 12" dia., bears S.50°W., 78 lks.
A pine, 10" dia., bears N.10°W., 65 lks.

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO rec Vol. 20 Pg 8407)

The cor. of secs. 8, 9, 16, & 17 is located by reference to the NE, SE, & NW BTs. All traces of the cor. and the SW tree have disappeared.
I reestablish the cor. in its orig. position as follows:
Set a granite stone 15x12x4", 10" in the ground for cor. of secs. 8, 9, 16, & 17 mkd with 4 notches on South & East edges; from which
A pinon, 14" dia., bears N.7°30'E., 72 lks., mkd: T32S R3W S9 BT.
A pinon, 12" dia., bears S.43°E., 160 lks., mkd: T32S R3W S16 BT.
A pinon, 6" dia. bears S.1°W. 69 lks. mkd: T32S R3W S17 BT
A pinon, 14" dia., bears N.3°30'W., 65 lks., mkd: T32S R3W S8 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Sept. 1969 - C.S. File 54/91-78

Found - 15x12x4" Stone, firmly In ground, no good marks visible.
14" Pine, now down & burnt, N.7½°E. 47.5 ft.
6" Pine, now down, S.1°W. 45.5 ft., shows scar.
14" Pine, now stob, N.3½°W. 42.9 ft. scribe visible.
No trace of SE BT.
Set - Brass Cap at Cor Mkd: County Surveyors T32S R3W
Office S 8 | S 9
1969 S 17 | S 16
New BTs- 12" D.Fir N.30°W. 7.9 ft. mkd: T32S R3W S8 CS BT.
14" D.Fir N.11°E. 27.9 ft. mkd: T32S R3W S9 CS BT.
10" D.Fir S.49°E. 16.5 ft. mkd: T32S R3W S16 CS BT.
15" D.Fir S.53°W. 13.9 ft. mkd: T32S R3W S17 CS BT.
Unrecorded -
17" Pine East 46.8 ft. scribe vis
12" Fir N.30°W. 7.9 ft., has scar. Do not open, but rescribe for new BT.