

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Leonard Herzstein, USFS & Deputy Co. Surveyor - Jim Landrum,
Witness - June & July 1981 - C.S. File 61/27-7

Found - 1" IP with Brass Cap, firmly set, projecting 14"
above ground mkd: County Surveyors Office T32S
R3W S5 S4 S8 S9 1970

BTs - A roothole (remainder of Orig. BT), bears S.70°E.,
23.8 ft., with a 32" D.Fir tree alongside,
rescribed by G. Wenderoth, Deputy County Surveyor
in 1955, with scribe marks S9 CS BT visible on
partly healed double blaze.

20" D.Fir stump bears S.41°W., 69.2 ft., with scribe
marks S8 CS BT visible on partly healed double
blaze.

A roothole bears N.58°W., 53.8 ft., with scribe
marks S5 CS BT visible on partly healed double
blaze.

A Madrone root crown (size indeterminate) 1970
bears S.28°W., 55.9 ft. (REC 58.2 ft.).

24" D.Fir stump bears N.54°W., 53.8 ft. (REC 47.0
ft.), with no marks visible.

New BTs- 6" Hemlock bears N.13¼°E., 44.5 ft., scribed T32S
R3W S4 CS BT on a double blaze. (Base of lower
blaze is 3.0 ft. above ground

6" Hemlock bears S.74°E., 55.4 ft., scribed T32S R3W
S9 CS BT on a double blaze.

6" D.Fir bears S.65°W., 58.2 ft., scribed T32S R3W
S8 CS BT on a double blaze.

6" D.Fir bears N.12°W., 34.0 ft., scribed T32S R3W
S5 CS BT on a double blaze. (Base of lower blaze
is 3.0 ft. above ground.