

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8368)</p> <p>-----</p> <p>Set ¼ sec. post, from which A pine, 30" dia., bears S.50°E., 39 lks. A fir, 5" dia., bears S.80°W., 37 lks.</p>
<p>Douglas Co. Surveyors Office - George J. Wenderoth, Deputy - Oct. 1955 - M41-10 & C.S. File 47/17</p> <p>-----</p> <p>Found pine stump S.50°E., 25.7 ft., scribe marks showing. Drive 1" iron pipe Scribe - 14" Hawthorne S.40°W., 91.3 ft. 26" Fir stump N.52°46'E., 97.7 ft. No other trees near.</p>
<p>Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1969 - C.S. File 54/91-70</p> <p>-----</p> <p>Found - 1" iron pipe at corner. 1955 14" Hawthorne, now dead, S.40°W., 91.3 ft. scribe visible. 26" Fir stump N.52°E., 97.7 ft. scribe visible. New BT - 15" D.Fir N.72°W., 30.0 ft. mkd: "¼ S5 CSBT" 8" D.Fir N.28°E., 21.0 ft. mkd: "¼ S4 CSBT" Fence corner bears N.19°W., 13.2 ft. fence runs north & east.</p>
<p>Don Garrett - For: USA - Nov. 1971 - M44-8</p> <p>-----</p> <p>Found - 1" I.pipe - Set Brass cap (in place) Stamped ¼ S4, S5, T32S R3W, R3W WM 1971, RLS 544 FC. Cor. bears N.19°W., 13.2' BTs FD - 14" Hawthorne (dead) S.40°W., 91.3 ft 26" Fir stump N.52°E., 97.7 ft. 15" D.Fir N.72°W., 30.0 ft. (scribing) 8" D.Fir N.28°E., 21.0 ft. (scribing)</p>
<p>Leonard Herzstein, U.S. Forest Service - Jim Landrum - Jim Hamilton - Nov. 30, 1981 - C.S. 61/29-38</p> <p>-----</p> <p>CONDITION REPORT ONLY Found - 3" dia. I.P. firmly set, projecting 8" above ground with brass cap marked T32S R3W WM. ¼ S5 S4 1971 RLS 544, set in 1971 by Don Garrett, L.S. #544. (M 44 - 8) 1" dia. I.P. alongside. A decayed Pine stump, size indeterminate, S.50°E., 25.7 ft. with no marks visible. continued next page</p>

