TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 328400

PRIMARY CORNER DESCRIPTION S 1/4 Cor. Sec. 16; only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8441)

Set a granite stone 15x15x12", 10" in the ground for ¼ sec. cor. on S bdy sec. 16 mkd. ¼ on N face, from which
A fir, 20" dia., bears N.18°E., 45 lks., mkd: ¼ S16 BT.
A fir, 20" dia., bears N.59°W., 25 lks., mkd: ¼ S16 BT.

Douglas Co. Surveyors Office - George J. Wenderoth, Deputy - Witness Clifford Worley - Oct. 1946 - Only record fd is Corner renewal #5 of the old system

---

Granite stone set for corner in place.
Both old BTs standing but dead.
Scribe A 6" Yew N.33°43'W., 76.7 ft.
A 16" Fir N.62°55'E., 58.1 ft.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Sept. 1969 - C.S. File 54/91-79

Found - Stone at corner, but no marks visible.
6" now 8" yew, N.33½°W., 76.7 ft. scribe visible.
16" now 24" W.Fir, N.63°E., 58.1 ft shows good scar.
Set Brass cap at cor. mkd: COUNTY SURVEYORS T32S R3W
OFFICE, 1969 ¼ S 16
Reblazed & rescribed -
24" W.Fir N.63°E., 58.1 ft. mkd: "¼ S16 CS BT"

Fd BC & 2 BTs, G. Baughman, 7/1975 - M56-20

Leonard Herzstein, USFS - Aug/Sept 2007 - M154-54 & C.S. 65/61-12

Found - 1¼" outside dia iron pipe firmly set, projecting 14" above the ground, with a 2½" dia brass cap (properly) marked
From which the BTs marked by Wenderoth in 1946
36" W.Fir, bears N.63°E., 58.4 ft, with healed double blaze. Tree was rescribed by Powell in 1969 (rec. 1946, N.62°55'E., 58.1 ft; 1969, 58.1 ft; 1975, N.64°E.)
12" yew, bears N.33½°W., 76.7 ft, with fragmentary scribe marks visible on partially healed double blaze (rec. 1946, N.33°43'W.; 1975, N.34°W., 76.6 ft)