

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO recs Vol 20 Pg 8419)  
-----  
Set a granite stone 16x12x10", 11" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
    A fir, 20" dia., bears N.10°E., 48 lks., mkd: ¼ S28 BT.  
    A fir, 48" dia., bears S.50°W., 50 lks., mkd: ¼ S33 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Sept. 5 1969 - C.S. File 54/91-75  
-----  
Found - 16x12x10 stone, mkd: "¼" on North face, firmly set at ¼ corner.  
    48" now 82" D.Fir, S.50°W., 33.0 ft shows faint scar  
    20" now 39" D.Fir, N.10°E., 31.7 ft shows good scar.  
Set Brass cap at corner mkd:  
    County Surveyors      T32S R3W  
    Office                    ¼ S 28      Doug. Co.  
    1969                      S 33      Jack. Co.

Reblazed and Rescribed:  
    82" D.Fir, S.50°W., 33.0 ft. mkd: "¼ S33 CS BT"

Jackson Co. Surveyors Office - Edward McGinty, County Surveyor - R. Frost, Tech. & S. Beecher, Tech - September 26, 1988 - C.S. file 63/82  
-----  
Found - 1969 Doug. Co. 2½" brass cap on 1" galv. I.P. projecting 12" above ground.  
    Orig. 1913 16x9x8" stone mkd. "¼" found alongside.  
    Orig. BT, a 40" D.Fir with healed blazes bears record, N.10°E. 31.7 ft to center of tree at base  
    Orig. BT, 82" D.Fir with scribe marks visible in partly exposed lower face bears record S.50°W., 33.0 ft. to center of tree at lower blaze.  
New BT - 6" Hemlock bears S.29°E., 9.7 ft. to center of tree at lower blaze. Corner lies an estimated 120 ft. east of the East Fork of Applegate Creek and about 350 ft. west of location marker on 36" dia. fir alongside road c. N.5°E., and southeast.

John Ransom, USFS - Jonathan Drew - 11/16/2011 - C.S. File 65/72-44  
-----  
Found - 2.5" Brass Cap on 1.25" G. Iron Pipe Projecting 13" above ground mkd "County Surveyors Office 1969""Doug Co. Jack Co.""T32S R3W ¼ S28 S33" ¼ Stone lays alongside to SW

continued next page

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

40" Fir Stump N.9°E., 32.0 ft healed blaze.  
82" Fir Stump S.53°W., 34.1 ft partially healed blaze.  
12" Hemlock S.30°E., 9.5 ft healed double blaze  
Painted BT's and Brushed from corner to BT's  
New BT - 9" Fir bears S.51°W., 8.5 ft mkd "¼ S33" "BT" on double blaze, brass washer nailed to lower face "LS 2561"  
Note - From Interstate take exit 87 East to Red Apple Road, Forest Rd 3231, follow spur road 500 to South Edge of Clear Cut Unit, follow unit edge 350 ft West to Corner falls 120 ft East of Creek on West facing slope.  
LAT/LONG POSITION DATA - SYSTEM: NAD83 CORS 96 EP:2002  
North 42°45'07.7015726" West 123°03'31.1807564"  
Estab. By: OPUS BASE-- RTK TIE