

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8439)

Set a granite stone 14x8x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 14" dia., bears N.62°E., 41 lks., mkd: ¼ S21 BT.
A fir, 14" dia., bears S.84°E., 91 lks., mkd: ¼ S28 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1988 - C.S. File 54/91-30

Found - 14x8x6" Stone, firmly set mkd: "¼" on north face. 14", now 28" D.Fir, N.62°E. 27.1 ft., shows good scar.
14", now 21" D.Fir, S.84°E., 60.1 ft., shows BT scar low on tree, upper part of tree, cat face.
Set - Brass Cap at Cor. Mkd: County Surveyors T32S R3W Office S 21 1969 S 28
New BT - 10" Pine S.71°W. 9.8 ft. mkd: "¼ S28 CS BT".

John Ransom, USFS - Jonathan Drew - 11/16/2011 - C.S. File 65/7243

Found - 2.5" Brass Cap on 1.25" G. Iron Pipe Projecting 13" above ground mkd "County Surveyors Office 1969""T32S R3W ¼ S21 S28"
35" Fir N.62°E., 27.0 ft., illegible Axe work and healed double blz
27" Fir S.84°E., (60.1 ft) record distance, healed blaze.
11" Pine S.71°W., 10.1 ft healed double blaze
No New Accessories Taken
Note - Flagged Cap, Brushed Path From Road
Painted BTs and Brushed from corner to BTs
From Interstate take exit 87 East to Red Apple Road, Forest Rd 3231, follow to Spur Road 400 to northern most point, walk uphill NW about 120 ft to Corner.

LAT/LONG POSTION DATA SYSTEM: NAD83 CORS 96 EP:2002
North 42°45'44.1583568" West 123°02'41.0559999"
Estab. By: OPUS BASE -- Traverse/RTK TIE