TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8369)

Set ¼ sec. post, from which
A cedar, 30" dia., bears N.5°E., 20 lks.
A Fir, 4" dia., bears S.18°W., 10 lks.

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8409-10)

Intersect the point for ¼ sec. cor., located by reference to the NE BT. All other traces of the cor. have disappeared. I reestablish this cor. in its orig. position, as follows:
Set a granite stone 16x8x6", 11" in the ground for ¼ sec. cor. mkd: ¼ on N face, from which
A cedar, 30" dia., bears N.5°E., 22 lks., mkd: ¼ S9 BT.
A fir, 12" dia., bears S.42°E., 17 lks., mkd: ¼ S16 BT.

Douglas Co. Surveyors Office - George J. Wenderoth, Deputy - Witness Clifford Worley - Oct. 1946 - Only record fd is Corner renewal #4 of the old system

---

Granite stone set for corner in place.
Orig. BT A 30" Cedar N.1°E., 14.5 ft.
Scribe A 5" Sugar Pine S.53°55'E., 18.7 ft.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Sept. 1969 - C.S. File 54/91-82

Found - 16x8x6" stone, firmly in ground, "¼" on north face.
30", now 39" Cedar N.1°E., 14.5 ft. scribe visible.
5" now 7" Pine S.54°E., 18.7 ft. shows good scar.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1969 T32S R3W ¼ S 9 / S 16

All BTs OK & tagged.

Jim Artman, LS 2268 - For: USFS - Jan. 1991 - C.S. 63/124

Found - 1" iron pipe with a 2¼" brass cap 12" above ground, granite stone alongside. 1946 & 1969
40" cedar bears N.1°E., 14.5 ft. scribes partially vis.
7" pine (dead) bears S.54°E., 18.7 ft healed blazes.
New BT - 12" D.Fir bears S.77°W., 11.8 ft. scribed "¼ S16 BT" with alum. washer marked "ARTMAN RLS 2268" nailed flush to BT face.