

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8433)

Set a basalt stone 18x14x8", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A Yellow Pine, 24" dia., bears S.1°30'E., 71 lks., mkd: ¼ S27 BT.
A cedar, 36" dia., bears S.3°W., 79 lks., mkd: ¼ S28 BT.
Miller's house, bears S.87°W., 37.00 chs.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1969 - C.S. File 54/91-66

Found - Corner Stone, 16x12x10" mkd: "¼" on west face.
Orig. 24", now 29" Y.Pine, S.1½°E., 46.9 ft., scribe visible.
Orig. 36", now down, S.3°W., 52.1 ft.
Set Brass Cap at Cor. mkd: County Surveyors T32S R3W
Office, 1969 ¼ S 28 | S 27
New BT - 6" D.Fir S.28°W., 7.8 ft. mkd: "¼ S28 CS BT"

John Ransom, USFS - Jonathan Drew - 11/16/2011 - C.S. File 65/72-45

Found - 2.5" brass cap on 1.25" G. iron pipe projecting 13" above ground marked "County Surveyors Office 1969""T32S R3W ¼ S28 S27"
30" Pine S.1½°E., 47.1 ft scribe fragments visible on partially healed double blaze.
11" Fir S.28°W., 5.3 ft healed double blaze
Painted BTs and Brushed from corner to BTs
No New Accessories Taken
Note - From Interstate take exit 87 East to Red Apple Road, Forest Rd 3231, to Spur Road 390 approx. .75 miles follow to ribbon at east edge of road, follow brushed Traverse Line 120 ft East to corner.
LAT/LONG POSITION DATA - SYSTEM NAD83 CORS 96 EP:2002
North 42°45'33.7707287" West 123°02'56.2091521"
Estab. By: QPUS BASE -- Traverse/RTK TIE