

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 400320

PRIMARY CORNER DESCRIPTION S 1/16 Secs. 21 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Glenn Baughman - For: USFS - 8/1974 - M49-69 & C.S. 55/357-13

Found - 1" iron rod (very old) 4.27 ft East of Sec. Line,
and 0.54 ft North of new corner.

Set - A 36" long, 2½" galv. iron pipe 32" in the ground,
in a mound of stones, with a 4" brass cap mkd:

S 1/16

S 21|S 22

RLS 536 1974

BTs - A hemlock, 8" dia. bears N.6°W. 26.9 ft scribed S
1/16 S 21 (BT) with brass washer stamped RLS 536

An alder, 12" dia. bears N.68°E., 25.4 ft scribed S
1/16 S 22 (BT) with brass washer stamped RLS 536

Corner lies in flat approximately 50 ft West of Applegate
Creek.

Fd. BC & 2 BTs by G. Baughman - 7/1975 - M56-20

Leonard Herzstein, USFS - Jim Landrum & Jim Hamilton - May 4,
1982 - C.S. 61/32-16

Found - 2½" IP with 1974 brass cap properly mkd. firmly set
flush with 1 ft dia. mound of stone.

12" half dead alder, N.68°E., 25.4 ft. with scribe
marks "S 1/16 S22 BT" and brass washer stamped
"RLS 536" visible on partly healed double blaze.

8" hemlock stump, N.03½°W., 26.9 ft. (rec. N.06°W.,
26.6 ft.) with scribe marks "S 1/16 S21 BT" and
brass washer stamped "RLS 536" visible on partly
healed blaze.

1" iron rod, bears N.82°E., 4.3 ft. projecting 8"
above ground.

New BTs- 10" yew, S.28°E., 8.7 ft. scribed "S 1/16 S22 CS BT"
on double blaze.

8" W. fir, N.79¼°W., 88.1 ft. scribed "S 1/16 S21 CS
BT" on double blaze.

6 ft. steel fence post, North 2.0 ft. with USFS
signs #54-2 and #54-9 attached.

Corner is about 25 ft. west of Applegate Creek.