

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8435)

-----  
Set a granite stone 15x8x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which  
A fir, 36" dia., bears N.55°E., 61 lks., mkd: ¼ S22 BT.  
A fir, 28" dia., bears N.14°W., 74 lks., mkd: ¼ S21 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-2

-----  
Found - 15x8x6" stone marked with a "4" visible.  
36" now 46" D.Fir N.55°E., 40.3 ft. shows good scar.  
28" D.Fir now stump, N.14°W. 48.8 ft scribe visible.  
Set brass cap at cor. mkd: COUNTY SURVEYORS T32S R3W  
OFFICE 1969 ¼ S 21|S 22  
New BT - 10" Laurel N.3°E., 40.5 ft. mkd: "¼ S22 CS BT"  
This corner lies on steep southeast slope. No trees within reason to Sec. 21.

Leonard Herzstein, USFS - Jim Landrum & Jim Hamilton - May 3, 1982 - C.S. 61/32-14

-----  
Found - 1" I.P. with 1969 County brass cap properly marked, firmly set projecting 16" above ground, leaning slightly SE, set by Powell  
Orig. 46" D.Fir, N.55°E., 39.4 ft. (Rec. 40.3 ft.) with healed blaze.  
Orig. 28" D.Fir stump, N.14°W., 48.8 ft. to face with old axe marks visible on decayed blaze.  
A 10" madrone, N.3°E., 40.1 ft. (Rec. 40.5 ft.) with scribe marks "¼ S22 CS BT" visible on partly healed blaze.  
New BT - A 7" P. Pine, N.77°W., 23.8 ft. scribed "¼ S21 CS BT" on double blaze.  
Note - Corner lies on steep SE slope about 150 ft. west of USFS Rd. #3231