TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION CC Secs. 21 & 22 (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8435)

Intersect S. bdy. of sec. 15, N.89°48'E., 12.90 chs. from the cor. of secs. 15 & 16.
At the point of intersection, I
Set a granite stone, 18x8x6", 12" in the ground, for closing cor. of secs. 21 & 22, marked CC on S with 3 grooves on E face; from which
A fir, 40" dia., bears S.43°E., 56 lks., mkd: T32S R3W S22 BT.
A fir, 18" dia., bears S.50°W., 173 lks., mkd: T32S R3W S21 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-11

Found - 18x8x16" Stone mkd. C C on south face, firmly set.
40", now 48" D.Fir, S.43°E., 37.0 ft., shows good scar.
18", now 25" D.Fir, S.50°W., 114.2 ft., shows good scar.
Set Brass Cap at Cor. Mkd: County Surveyors Office 1969 C C T32S R3W S 15 / S 21 | S 22
New BT - 6" Hemlock S.4°W. 14.0 ft mkd: T32S R3W S21 CC CS BT
This corner lies in heavy undergrowth, about 80 ft. S of E-W ravine.