

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8366)

-----  
Set post, cor. to secs. 9, 10, 15, & 16, from which  
A Fir, 30" dia., bears N.5°E., 40 lks.  
A Laurel, 6" dia., bears S.80°E., 25 lks.  
A Fir, 12" dia., bears S.30°W., 41 lks.  
A Laurel, 8" dia., bears N.80°W., 38 lks.

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO rec Vol. 20 Pgs 8405-6)

-----  
The cor. of Secs. 9, 10, 15 & 16, is located by reference to the NE, SW, and stump of the NW BTs. All other traces of the cor. have disappeared. I reestablish the cor. in its original position as follows:

Set a granite stone, 15x15x12", 10" in the ground, for cor. secs. 9, 10, 15 and 16, marked with 4 notches on S and 3 notches on East edge; from which  
A Fir, 30" dia., bears N.2°E., 40 lks. mkd T32S R3W S10 BT  
A Fir, 20" dia., bears S.1°E., 57 lks. mkd T32S R3W S15 BT  
A fir, 18" dia. bears S.34°W., 42 lks mkd: T32S R3W S16 BT  
A fir, 18" dia., bears N.43°W., 59 lks mkd: T32S R3W S9 BT

Douglas Co. Surveyors Office - Ben B. Irving, Co. Surveyor - Jan 1945 - C.S. File 38/41

-----  
Granite stone set for corner as orig. 15x15x12" 10" in the ground. Found orig. BT as follows:  
20" Fir S.1°E., 57 lks.  
18" Fir N.43°W., 59 lks.  
Set the following new trees:  
5" Sugar pine S.75°E., 6 lks. T32S R3W S15 CS BT  
6" Madrona N.77°W., 29 lks. T32S R3W S9 CS BT

Glenn S. Baughman - For: Andrew Koch - March 1969 - M37-45

-----  
Found - Granite stone as record in 1945  
22" Fir bears S.0°30'E. 36.1 ft visible bark scribe.  
10" S.Pine bears S.75°E., 4.0 ft. scribe visible.  
8" Laurel bears N.77°W., 19.1 ft., closed face.  
24" Fir stump bears S.1°E., 38.6 ft., scribe visible.  
Set - 1½"x30" galv. IP with brass cap & stamped: Sec. Cor. 9, 10, 15, & 16, T32S R3W, WM  
New BT - Scribe 10" Laurel bears N.57°30'E., 18.9 ft.  
**Added 9/10/1969 DCSO - 6" D.Fir N.54°W., 17.9 ft. mkd: T32S R3W S9 CS BT (C.S. 54/91-83)**

cont.

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Glenn Baughman - For: USFS - Nov. 1979 - C.S. 58/176-18A  
-----

Found - 1" IP firmly set, projecting 12" above ground with  
a 2½" Brass cap mkd: "T32S R3W WM 9 10 15 16 1969  
536" From which:  
Orig. BT, a 32" D. Fir stump, scribe marks "BT"  
visible, bear N.2°E., 26.4 ft.  
A 20" D.Fir stump scribe marks "R3W S9 BT" visible,  
bears N.43°W., 38.9 ft. to face.  
A 24" D.Fir, w/healed blaze, bears S.1°E., 37.6 ft.  
A 16" Sugar pine, with healed blaze, bears S.75°E.,  
4.0 ft.  
A 10" Madrona, with healed blaze, bears N.77°W.,  
18.1 ft. (Record 19.1 ft.)  
A 10" Laurel, scribe marks "T32S R3W S10 BT" visible  
bears N.57½°E., 18.9 ft.  
A 10" D.Fir with healed blaze, bears N.54°W. 17.9 ft  
New BT - A 24" D. Fir, bears S.41°W., 47.9 ft. marked "T32S  
R3W S16 BT" on a double blaze and nailed a brass  
washer stamped "LS 536 into lower blaze.