

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8365)

Set post, cor. to secs. 3, 4, 9, & 10, from which
A fir, 16" dia., bears N.70°E., 14 lks.
A Maple, 6" dia., bears S.60°E., 40 lks.
A Fir, 24" dia., bears S.64°W., 67 lks.
A Fir, 10" dia., bears N.65°W., 48 lks.

Douglas Co. Surveyors Office - Ben B. Irving, Co. Surveyor - Jan 1945 - C.S. File 38/41

Set a 2"x54" pipe 48" in ground.
Location set from old BTs
30" Fir N.70°E., 14 lks.
20" Fir N.65°W., 48 lks.
30" Fir S.64°W., 69 lks. (Snag)
Set new trees
27" W.Fir S.64°W., 50.5 ft.
14" W.Fir S.56°E., 53.0 ft.

Douglas Co. Surveyors Office - James W. Byron, Deputy - For: Douglas Co. Rd. Dept. - Jan. & Feb. 1957 - C.S. 48/36 (C.S. 48 drawer is a Co. Rd drawer & it is filed as Co. Rd. 36)

Found - 2" IP at corner.
The N.70°E., 14 lks. BT alive & fair condition. All other BTs are dead.
Blaze & scribe:
22" yewood bears S.2°E., 184.4 ft S10 T32S R3W CS BT
26" W.Fir bears S.89½°W., 140.0 ft S9 T32S R3W CS BT
21" W.Fir bears N.44½°W., 96.8 ft. S4 T32S R3W CS BT

Glenn S. Baughman - For: Andrew Koch - March 1969 - M37-45

Found - 2" IP - 1957
30" W.Fir bears S.89°W., 140.0 ft., tag & scar.
20" Fir snag bears N.70°E., 9.3 ft., tag & closed face.
24" Yew wood bears S.2°E., 184.4 ft., tag & scribe visible.
Set - 1½"x30" galv. IP & brass cap, stamped Sec. 3, 4, 9, & 10 T32S R3W, WM
Scribed 20" W.Fir bears N.84°E., 28.9 ft.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

Leonard Herzstein, USFS & Deputy Douglas Co. Surveyor - Jim Landrum, witness - Oct. 15, 1981 - C.S. File 61/29-14

Found - 1½" I.P., firmly set, projecting 4" above ground, with B.C., mkd 1969 Renewal, with 2" I.P. alongside (1945).

BTs - Remains of orig. BTs:
30" W.Fir snag bears N.70°E., 9.3 ft. w/fragmentary scribe marks visible on previously opened blaze & rescribed by Byron in 1957, w/scribe marks W CS BT visible on bark blaze.

Decayed W.Fir stump, size indeterminate, bears N.65°W., 31.7 ft. with no marks visible.

B. Irving's BT s marked in 1945

Decayed W.Fir stump, size indeterminate, bears S.64°W., 50.5 ft. with no marks visible.

J. Byron's BT s marked in 1957

23" Yew-wood bears S.2°E., 184.4 ft., with scribe marks S10 T32S R3W CSBT visible on partly healed double blaze.

35" W.Fir bears S.89½°W., 140.0 ft. with healed double blaze.

G. Baughman's BT's in 1969

20" Fir snag bears N.84°E., 29.9 ft. (Rec. 28.9 ft.), with scribe marks T32S R3W S3 BT visible on partly healed double blaze.

New BTs- 6" W. Fir bears N.82½°E., 39.9 ft., scribed T32S R3W S3 CSBT on double blaze.

No suitable trees in Sec. 4.

Note - Corner is in East-West fence line, approx. 100 ft. S.70°W. of the confluence of Dismal and Cow Creeks; and is 30 ft. South of the top of the South bank of Cow Creek.