

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8365)

Set ¼ sec. post, from which
A fir, 12" dia., bears N.80°E., 17 lks.
A fir, 24" dia., bears N.80°W., 29 lks.

Douglas Co. Surveyors Office - George Wenderoth, Deputy - 9/1947 - C.S. File 45/226

1" I. Pipe
OBT fallen
6" Yew S.44°W., 54.8 ft.
6" Madrone S.76°24'E., 26.5 ft.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-23

Found - 1" IP at ¼ cor. 1947
6" now 7" Yew S.44°W., 54.8 ft. scribe visible.
No trace of SE BT
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T32S R3W
OFFICE 1969 ¼ S 4|S 3
New - 46" D.Fir S.15°E., 19.6 ft. mkd: ¼ S3 CS BT.
Fence corner (fence running S & W) bears N.71°E., 16.0 ft.

Leonard Herzstein, USFS & Dep. Co. Surveyor - Randy Lopez & Jim Hamilton, Witnesses - Nov. 25, 1981 - C.S. File 61/29-35

CONDITION REPORT ONLY.
Found - 1¼" I.P., firmly set, projecting 14" above ground w/B.C., properly marked, with 1" I.P. alongside.
BTs - 6", now 7" Yewwood bears S.44°W., 54.8 ft., w/scribe marks: "¼ S4 CSBT" visible on partly healed double blaze. 1969
46" D.Fir bears S.15°E., 19.6 ft. w/scribe marks: "¼ S3 CS BT" visible on partially healed blaze. 1969
Note: Fence corner bears N.71°E., 16.0 ft., w/fence running South & West. Corner is about 100 ft. NW of dirt road.

Fd. Ok 10/1994, M121-13
Fd. OK by D Hitner - 8/2016 - M172-44