

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8418)

Set basalt stone 12x10x5", 8" in the ground for 1/4 sec. cor. mkd. 1/4 on North face, from which
A fir, 30" dia., bears N.14°W., 10 lks., mkd: 1/4 S27 BT.
A hemlock, 8" dia., bears S.20°E., 6 lks., mkd: 1/4 S34 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1969 - C.S. File 54/91-67

Found - Corner Stone, 12x10x5, firmly set, mkd. "1/4" on north face.
Orig. 30", now 38" D.Fir, N.14°W. 6.6 ft., shows good scar.
Orig. 9" Hemlock, now stob, S.20°E. 4.0 ft., opened for scribe.

Set Brass Cap at Cor. Mkd: County Surveyors T32S R3W
Office Doug. Co. 1/4 S 27
1969 Jack Co. S 34

New BT - 8" Hemlock S.42°E., 22.7 ft. mkd: "1/4 S34 CS BT"