

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8434)

Set a serpentine stone 18x10x8", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A cedar, 6" dia., bears N.2°W., 38 lks., mkd: ¼ S22 BT.
A cedar, 8" dia., bears S.40°W., 56 lks., mkd: ¼ S27 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - 8/5/1969 - C.S. File 54/91-44

Found - 18x10x8" Stone, mkd: "¼" lying downhill from corner. 8", now 19" Cedar, S.40°W., 37.0 ft., opened for scribing.
6", now 19" Cedar, N.2°W., 25.1 ft., shows very faint scar.

Set Brass Cap at Cor. Mkd: County Surveyors T32S R3W
Office ¼ S 22
1969 S 27

Reblazed. & Rescribed -
19" Cedar N.2°W., 25.1 ft., mkd: ¼ S22 CSBT.
New BT - 6" D.Fir S.50°W., 8.9 ft. mkd: ¼ S27 CSBT.
This corner lies on very steep west slope at head of ravine, running W.