

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

| |
|---|
| <p>GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8366)</p> <p>-----</p> <p>Set ¼ sec. post, from which A fir, 5" dia., bears N.70°W., 17 lks. A fir, 5" dia., bears S.30°W., 14 lks.</p> |
| <p>Douglas Co. Surveyors Office - A.R. Evans, Deputy - R.G Irving & J.I Clinton, Witnesses - Feb 1951 - M8-2; C.S. File 44/92; Vol. 5 Pg. 39</p> <p>-----</p> <p>Set - 3/4" iron rod by proportionate measurement at root of new BT. A 72" Fir, face bears South 3.2 ft. mkd: ¼ S15 CS BT. 30" fir N.59°E., 24.6 ft. mkd: ¼ S10 CS BT.</p> |
| <p>Glenn S. Baughman - For: Andrew Koch - March 1969 - M37-45</p> <p>-----</p> <p>Found - 30" D.Fir BT, bears N.59°E., 24.6 ft., bark scribe visible. ¾" I.R., see 1951 ren.</p> <p>Set - 1½" galv. IP & brass cap and stamped: ¼ Cor. 10, 15, T32S R3W WM</p> <p>New BT - Scribed: 10" I.Cedar, S.61°E., 19.1 ft.</p> |
| <p>Leonard Herzstein, USFS & Dep. Co. Surveyor - Jim Landrum, Witness - July 8, 1981 - C.S. File 61/27-11</p> <p>-----</p> <p>Found - 1¼" I.P., with Brass Cap, firmly set, projecting 12" above ground, marked:, T32S R3W W.M. 1969 ¼ 10 15 OLS 536 with 3/4" I.Rod alongside.</p> <p>BTs - 34" D.Fir snag bears N.59°E., 24.6 ft. with scribe marks ¼ S10 CS BT visible on double bark blaze. 62" D.Fir stump bears South, 5.2 ft. (2.2 ft. to face) (rec 3.2 ft.) with scribe mark T visible on bark blaze. 15" I.Cedar bears S.61°E., 19.9 ft. (rec 19.1 ft.) with fragmentary scribe marks visible on partly healed blaze.</p> <p>New BTs- 14" D.Fir bears N.50¼°E., 36.0 ft., marked ¼ S10 CS BT on double blaze.</p> <p>Note - Corner is on top of spur ridge running North & is about 300 ft. East of main North-South ridge. Corner is 960 ft. West of Centerline of USFS Rd#3231.</p> |
| |