

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 cor. Secs. 3 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8365)

Set 1/4 sec. post, from which
 A fir, 12" dia., bears North, 15 lks.
 A fir, 10" dia., bears S.12°W., 11 lks.

Douglas Co. Surveyors Office - George Wenderoth, Deputy - 9/1947 - C.S. File 45/226

1" I. Pipe
 18" W.Fir S.15°W., 7.2 ft. OBT.
 14" W.Fir N.70°33'W., 62.9 ft.

Douglas Co. Surveyors Office - A.R. Evans, Deputy - R.G Irving & J.I Clinton, Witnesses - Feb 1951 - M8-2; C.S. File 44/92; Vol. 5 Pg. 39

Found corner pipe & 2 BTs - 1947
Marked new BT & scribed
 W.Fir S.22°W., 19.4 ft. mkd: ¼ S - 10 CS BT.

Glenn S. Baughman - For: Andrew Koch - March 1969 - M37-45

Found - 1¼" IP
 BTs, stumps, rotten, no scribes visible
Set - 1½"x30" galv. IP & Brass cap & stamped ¼ cor. 3, 10,
 T32S R3W WM
 Scribed: 10" W.Fir bears N.16°E., 80.7 ft.
 Scribed: 10" Fir bears S.9°W., 117.7 ft.

Fd. Ok L .Herzstein, 7/14/1981 - C.S. File 61/27-20