

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 466400

PRIMARY CORNER DESCRIPTION CC Secs. 14 & 15 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8364)

Set post, cor. to secs. 14, 15, 22, & 23, from which
A fir, 8" dia., bears N.70°E., 25 lks.
A fir, 8" dia., bears S.30°E., 34 lks.
A fir, 10" dia., bears S.15°W., 22 lks.
A fir, 30" dia., bears N.70°W., 15 lks.

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8402)

The corner of secs. 14, 15, 22, & 23, which is a decayed post, marked as described by the Surveyor General. The NW BT remains; the other BTs are dead & fallen. I destroy this cor. of Secs. 14 & 15 only, as follows:
Set a granite stone, 15x8x6" 10" in the ground for cor. of secs. 14 & 15 only, marked with 2 notches on East edge, from which
A fir, 30" dia. bears N.60°E., 52 lks mkd: T32S R3W S14 BT
A fir, 40" dia. bears N.70°W., 18 lks mkd: T32S R3W S15 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-19

Found - 15x8x6" Stone lying on ground near corner mkd. with 2 notches.
Orig. 40", now 50" D.Fir, N.70°W. 11.9 ft., shows good scar, also faint bark scribe.
Orig. 30", now 38" D.Fir, N.60°E. 34.3 ft., shows good scar.
Set Brass Cap at Cor. mkd: County surveyors T32S R3W
Office S 15 | S 14
S 22
New BT - 14" D.Fir S.52°E., 47.1 ft. mkd: T32S R3W S22 CS BT.