

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8417)

Set a basalt stone 15x8x8", 10" in the ground for cor. of secs. 26, 27, 34, & 35 mkd with 1 notch on South & 2 notches on East edge, from which

A fir, 20" dia. bears N.14°E., 7 lks. mkd: T32S R3W S26 BT
A fir, 16" dia. bears S.60°E., 26 lks mkd: T32S R3W S35 BT
A fir, 12" dia. bears S.45°W., 16 lks mkd: T32S R3W S34 BT
A fir, 18" dia. bears N.48°W., 11 lks mkd: T32S R3W S27 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1969 - C.S. File 54/91-68

Found - Corner stone, 15x8x8, firmly set mkd. with notches. Orig. 20" D.fir now stob N.14°E., 4.6 ft. scribe visible.
Orig. 18" D.Fir now stob N.48°W., 7.3 ft. found reverse scribe.
Orig. 12" D.Fir now burnt stob, S.45°W., 10.6 ft., stob flush with ground.
Orig. 16" D.Fir now stob, S.60°E., 17.2 ft. scribing rotted out.

Set brass cap at cor. mkd: COUNTY SURVEYORS T32S R3W
OFFICE DOUG CO S 27 | S 26
1969 JACK CO S 34 | S 35

New BTs- 6" hemlock S.18°W., 19.0 ft. mkd: T32S R3W S34 CS BT
6" hemlock S.66°E., 4.4 ft mkd: T32S R3W S35 CS BT
8" hemlock N.69°E., 5.9 ft. mkd: T32S R3W S26 CS BT
6" hemlock N.15°W., 20.2 ft. mkd: T32S R3W S27 CS BT

Jackson Co. Surveyors Office - Edward McGinty, Co. Surveyor - R Frost & S Beecher, Techs - Oct. 20, 1988 - C.S. 63/82-4

Found - Projecting 12" the 1" dia. galvanized iron pipe, with 2½" dia. brass cap (properly) mkd. set by the Douglas Co. Surveyor per Survey dated 1969. The original stone, mkd. with cross on top, recorded by F Mensch, in 1913, is found deposited (buried) alongside corner.

Original bearing trees fd. as follows:
Sawed fir stump, 25" dia., containing scribe mks. brs. N.18°E., 5.45 ft. to center. Record; N.14°E., 4.62 ft.
The center of rotted fir stump, 20" dia., brs. record; S.60°E., 17.16 ft.

continued next page

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The middle of rotted fir stump remains, brs. record;
S.45°W., 10.56 ft.
Rotted fir stump, 24" dia., containing reverse
impression of scribe mks. including "BT", brs.
N.40°30'W., 8.2 ft. to center. Record; N.48°W.,
7.26 ft.
Bearing trees mkd. by Douglas County in 1969 fd. and
measured to center of trees near base:
Hemlock, 12" dia., with scribe mks. visible in
partially healed blaze, brs. N.69°E., 6.4 ft.
Record; 5.9 ft.
Hemlock, 10" dia., containing scribe mks. in partly
exposed face, brs. S.66°E., 4.60 ft. Rec; 4.40 ft
Hemlock, 11" dia., with healed blaze, brs. S.18°W.,
18.3 ft. Record; 19.0 ft.
The NW BT is now gone. As there is no suitable tree
in Sec 27.
Set - A 5/8x24" rebar, 23" in the ground with yellow
plastic cap, mkd. "Jackson CS.", located 6 ft.
South of a 28" dia. fir stump, brs. N.1°18'W.,
48.59 ft.
Corner lies at top of cut-bank, 8 ft. above and 30 ft. South
of middle of road, C. S.50°W. and about 6 ft. South of
location marker on original NE BT (stump) alongside road.