TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8427-8)

Set a serpentine stone 15x10x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A sugar pine, 12" dia. bears S.27°E., 17 lks mkd: ¼ S26 BT
A cedar, 6" dia., bears S.88°W., 23 lks., mkd: ¼ S27 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1969 - C.S. File 54/91-69

Found - Corner Stone, 15x10x6, in place & mkd.
Orig. 12",now 24" Y.Pine, S.27°E. 11.2 ft., shows good axe face.
Orig. 6", now 12" Cedar, S.88°W., 15.2 ft., shows good scribing.
Set Brass Cap at Cor. mkd: County Surveyors Office, 1969 T32S R3W ¼ S 27|S 26
No new Bearing Trees needed.
This corner lies about 40.0 ft. N of small creek on SW slope.