

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8428)

-----  
Set a serpentine stone 15x10x8", 10" in the ground for cor. of secs. 22, 23, 26, & 27 mkd with 2 notches on S & E edges, from which  
A cedar, 8" dia., bears N.70°E., 42 lks., mkd: T32S R3W S23 BT.  
A fir, 7" dia. bears S.47°E., 43 lks. mkd: T32S R3W S26 BT  
A cedar, 15" dia., bears S.69°W., 39 lks., mkd: T32S R3W S27 BT.  
A fir, 24" dia. bears N.22°W., 21 lks mkd: T32S R3W S22 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-36

-----  
Found - 15x10x8" Stone, firmly set, 2 notches on South & East Sides.  
8", now 18" Cedar, N.70°E. 27.7 ft., shows good scar  
7", now 13" W.Fir, S.47°E. 28.4 ft., shows good scar  
15", now 29" Cedar, S.69°W. 25.7 ft. shows good scar  
24", now 28" D.Fir, N.22°W. 13.9 ft. shows good scar  
Set Brass Cap at Cor. mkd: County Surveyors T32S R3W  
Office S 22 | S 23  
1969 S 27 | S 26

All Bearing Trees OK and Tagged.