

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8429-30)

-----  
Set a serpentine stone 16x10x8", 11" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which  
A cedar, 16" dia., bears S.3°E., 24 lks., mkd: ¼ S23 BT.  
A Y.Pine, 24" dia., bears S.15°W., 18 lks., mkd: ¼ S22 BT.

-----  
Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-16

-----  
Found - 16x10x8" Corner stone Mkd "¼" on west face.  
Orig. 16", now 21" Cedar S.3°E. 15.8 ft., shows good face.  
Orig. 24", now 30" Y.Pine, S.15°W. 11.9 ft., shows good scribing.

Set Brass Cap at Cor. mkd: County Surveyors T32S R3W  
Office, 1969 ¼ S 22|S 23

This corner lies on a steep northwest slope.  
No New BTs needed.