

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION CC Secs. 22 & 23 only (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8430)

-----

Set a granite stone 14x12x4", 9" in the ground for cor. of secs. 22 & 23, mkd CC on S, with 2 grooves on E face; from which

A fir, 24" dia. bears S.76°E. 27 lks. mkd: T32S R3W S23 BT

A fir, 24" dia. bears S.30°W. 20 lks. mkd: T32S R3W S22 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-20

-----

Found - 14x12x4" Stone, firmly set with CC mkd. on south face.

Orig. 24", now 38" D.Fir, S.76°E. 17.8 ft., shows good scar.

Orig. 24", now 34" D.Fir, S.30°W. 13.2 ft., shows good scar.

Set brass Cap at C. Cor. Mkd: County Surveyors Office  
1969

T32S R3W  
S 14  
S 22 | S 23

New BT - 8" Hemlock N.42°E. 19.2 ft. mkd: T32S R3W S14 CS BT.