

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8362)

Set post, cor. to Secs. 2, 3, 10, & 11, from which
A Laurel, 6" dia., bears N.72°E., 19 lks.
A Cedar, 15" dia., bears S.30°E., 64 lks.
A Fir, 10" dia., bears S.30°W., 9 lks.
A Live Oak, 5" dia., N.32°W., 28 lks.

Douglas Co. Surveyors Office - A.R. Evans, Deputy - Ray G. Irving, J.I. Clinton, & Gordon Foster, crew - Feb. 1951 - M8-2, C.S. File 44/92 & Vol. 5 Pg. 39

Found - Granite and stone with cross.
2 OBTs 10" Fir (now 20") S.30°W. 9 lks (chopped out)
15" cedar (now 24".) S.30°E., 64 lks. (Rescribe)
Blaze & scribe new BTs
14" Fir N.83°E., 31 ft. mkd: T 32 S R 3 W S 2 CS BT
60" Fir N.23°W., 54.0 ft mkd: T 32 S R 3 W S 2 CS BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - 7/10/1969 - C.S. File 54/91-10

Found - Large Stone at Section Corner, 1951
Orig. 16", now 36" Cedar, S.25°E. (Rec. S.30°E., 42.2 ft., faint bark scribe visible.
Orig. 10", now 27" Fir, S.30°W., 5.9 ft., prev. opened, pitched over scribe visible.
14", now 16" Fir, N.83°E., 31.0 ft., shows good scar.
60", now 60" D.Fir, N.23°W., 54.0 ft., bark scribe visible.
Set brass cap at Cor. mkd: County Surveyors T32S R3W
Office S 3|S 2
1969 S 10|S 11
New BT - 8" D.Fir N.66°W., 11.5' mkd: T32S R3W S10 CS BT
Reblazed & rescribed -
27" D.Fir S.30°W., 5.9 ft. mkd: T32S R3W S10 CS BT.
36" Cedar S.25°E., 42.2 ft. mkd: T32S R3W S11 CS BT.

Fd. Ok by L. Herzstein, 7/13/1981 - C.S. file 61/27-17