

PRIMARY CORNER DESCRIPTION Sec Cor for 2 & 3; 34 & 35, T31-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7688)

Set post, cor. to secs. 2, 3, 34 and 35, from which
A Fir 12" dia., bears N.38°E., 19 lks. dist.
An Alder 4" dia., bears S.60°E., 34 lks. dist.
An Alder 14" dia., bears S.58°W., 47 lks. dist.
An Alder 24" dia., bears N.70°W., 19 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7719)

The Sec. cor., which is a post, greatly decayed, with marks nearly obliterated, I find the 4 witness trees. At cor. point, SET a stone 12x12x6 ins., 8" in the ground for cor. to secs. 2, 3, 34 and 35, marked with 2 notches on E. and 4 notches on W. edges; from which

A Fir (hemlock) 12" dia., now 14", bears N.38°W., 19 lks. dist. mkd. T31S R3W S35 BT.
An Alder 4" dia., bears S.60°E., 34 lks. dist. mkd. T32S R3W S2 BT.
An Alder 14" dia., bears S.58°W., 47 lks. dist. mkd. T32S R3W S3 BT. This tree is dead. In its stead:

I mark:

A Fir 14" dia., bears S.31°W., 22 lks. dist. "T32S R3W S3 BT"
An Alder 24" dia., bears N.70°W., 19 lks. dist. "T31S R3W S34 BT".

George J. Wenderoth, Deputy Co. Surveyor - June 1950 - C.S. File 45/229

Found - 28" Hemlock bearing N.38°E., 12.5 ft.
28" W.Fir S.31°W., 14.5 ft.
Set a 2" I.P. for the corner, from which marked:
A 6" Hemlock bearing S.36°10'E., 33.0 ft.
A 10" W.Fir bearing N.11°18'W., 11.5 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan/Feb. 1966 - C.S. File 52/63-68

Found - 28" Hemlock now 28", N.38°E., 12.5 ft. Tree almost dead.
28" W.Fir snag S.31°W., 14.5 ft. scribe visible
"T32S"

(Cont. Next Page)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

6" Hemlock, down, S.36°E., 33.0 ft. scribe visible
"S2 CS BT"
No trace of NW. BT.
No trace of iron pipe as recorded.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S
S 34 | S 35
S 3 | S 2
T 32 S
1966
New BTs- 49" D.Fir West, 66.3 ft. scribed T31S R3W S34 CS BT
10" Hemlock S.9°W., 27.0 ft. scribed T32S R3W S3 CS
BT.
20" Hemlock N.86°E., 25.2 ft. scribed T31S R3W S35
CS BT.

Leonard Herzstein, U.S.F.S. (Deputized by DCSO) - Wit: Rod
Riley; Art Arciniega - Aug. 14, 1980 - C.S. File 61/11-16

Found - 1966 County brass cap properly mkd., firmly set,
projecting 12" above ground on a 1¼" I.P.
Orig. 28" Hemlock snag, N.38°E., 12.5 ft. with
opened face, no marks visible.
Orig. 28" W.Fir stump S.31°W., 14.5 ft. with scribe
marks "T32S" visible on decaying blaze.
A 1948 Wenderoth BT, a root hole, S.36°E., 33.0 ft.
with 6" Hemlock alongside with scribe marks "S2
CS BT" visible on partly healed blaze.
1966 BT by Powell, a 20" Hemlock snag, N.86°E., 25.2
ft. with scribe marks "T31S R3W S35 CS BT"
visible on partly healed double blaze.
A 14" Hemlock, S.9°W., 27.0 ft. with healed double
blaze.
A 56" D.Fir West, 66.3 ft. with healed blaze.
New BTs- 14" Hemlock N.70°E., 46.0 ft. scribed T31S R3W S35
CS BT.
7" Hemlock S.38½°E., 45.2 ft. scribed T32S R3W S2 CS
BT.

Ron Quimby - Crew: N. Fromdahl, R Heichel & R Vincent -
3/2018 - C.S. File 65/101-27

Condition Report
Found - DCSO 2½" brass cap (properly mkd)
Rotted hemlock stump N.38°E., 12.5 ft. no marks.
Remnants of 20" Hemlock N.86°E., 25.2 ft.
18" Hemlock snag N.70°E., 46.0 ft. good scar.
continued next page

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec Cor for 2 & 3; 34 & 35, T31-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

14" Hemlock S.38°E., 45.2 ft. good scar.
24" Hemlock S.9°W., 27.0 ft. good scar.
60" D.Fir west 66.3 ft. good scar.
Post 3.0 East & West.
Note - Compass decl. 15½°E.