

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 526400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 14 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8431)

Set a slate stone, 18x10x4" 12" in the ground for 1/4 sec. cor. of sec. 14, only marked 1/4 on N face; from which
A fir, 28" dia., bears N.22°E., 24 lks., mkd: 1/4 S14 BT.
A fir, 24" dia., bears N.22°W., 34 lks., mkd: 1/4 S14 BT.

J. H. Markham, Jr - For: M & B Logging Co. - Wit: H.C. Stokes - Sept. 9, 1959 - C.S. File 42/35615

Found - 28" Fir Stump, logged, bears N.22°E. 15.8 ft. 0BT., I rescribed 1/4 S14 BT.
24" Fir Stump bears N.22°W. 22.4 ft. 0BT, I rescribed 1/4 S14 BT.
At Corner Point found Orig. Stone & Set 3/4"x30" Iron Pipe from which:
26" Fir Stump, logged, bears S.22°W. 15.5 mkd. 1/4 S BT.
End of Spur Road and Landing bears S.44°W. approx. 450.0 ft. distance.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-18

Found - 3/4" Iron Pipe at 1/4 Corner & Stone mkd. "1/4" on north side. 1958
28" D.Fir stump, burnt, N.22°E. 15.8 ft.
24" D.Fir Stump, N.22°W. 22.4 ft., scribe visible.
26" D.Fir Stump S.22°W. 15.5 ft., bark scribed.
Set brass Cap at Cor. mkd: County Surveyors T32S R3W
Office 1/4 S 14
1969

New Bearing Objects, as follows:
Set 5/8" I.Rod, bears N.41°W., 10.0 ft. from 1/4 BC.
Set 5/8" I.Rod, bears N.41°E., 10.0 ft. from 1/4 BC.
(Bearing between 2 set IR's is N.89°E., 13.3')
(Info for B0s taken from sketch in file)