

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8429)

Set a serpentine stone 16x8x5", 11" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 30" dia., bears N.52°E., 71 lks., mkd: ¼ S23 BT.
A cedar, 30" dia., bears S.42°W., 32 lks., mkd: ¼ S26 BT.

J. H. Markham, Jr - For: M & B Logging Co. - Wit: S.J. Pritchett - Nov. 9, 1958 - C.S. File 42/356-18

Found - 42" Fir N.50°E. 50.0 ft. O.B.T.
36" cedar S.37°W. 22.0 ft. O.B.T.
At Corner point Set 1"x30" Iron Pipe & fd stone from which:
6" W.Fir bears S.69°E., 8.3 ft. mkd. ¼ S26 BT
10" Fir bears N.71°E. 9.0 ft. mkd. ¼ S23 BT.
Road bears west 272.0 ft.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-17

Found - 16x8x5" Corner Stone and 1" Iron Pipe
Orig. 30", now 42" Fir Stump. N.50°E. 50.0 ft., shows good face.
Orig. 30", now 36" Cedar Stump, S.37°W. 22.0 ft., shows poor face.
Markham's 10" Fir, now 10 snag, N.71°E. 9.0 ft., shows burnt scribing.
DO NOT SET BRASS CAP
New BTs- 28" R.Fir N.9°W. 111.8 ft. mkd: ¼ S23 CS BT.
36" Cedar N.20°E. 115.8 ft. mkd: ¼ S23 CS BT.
This corner lies in a logging unit and no BTs. in range in Section 26. Also road bears West 272 feet.