

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8416)

-----  
Set a serpentine stone 18x12x7", 12" in the ground for cor. of secs. 25, 26, 35, & 36 mkd with 1 notch on E & S edges, from which  
A fir, 40" dia. bears N.55°E., 54 lks mkd: T32S R3W S25 BT  
A fir, 40" dia. bears S.15°E., 10 lks mkd: T32S R3W S36 BT  
A fir, 48" dia. bears S.35°W., 27 lks mkd: T32S R3W S35 BT  
A fir, 54" dia. bears N.44°W., 57 lks mkd: T32S R3W S26 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1969 - C.S. File 54/91-64

-----  
Found - Corner stone, 18x12x7" firmly set with unrecorded brass cap alongside mkd: State Bd. of Forestry  
T32S R3W  
S 26 | S 25  
S 35 | S 36  
RS 359  
1968  
40" D.Fir, now snag, N.55°E, 35.6 ft., scribe visible.  
40" D.Fir, 44" with broken top, S.15°E, 6.6 ft, shows good scar.  
48" D.Fir, now snag, S.35°W, 17.8 ft, scribe visible.  
54" now 72" D.Fir, N.44°W, 37.6 ft., shows good scar.  
New BTs- 17" Yellow Pine, N.21°E., 31.5 ft mkd: "T32S R3W S25 CS BT".  
18" D.Fir, S.70°W., 40.2 ft. mkd: "T32S R3W S35 CS BT".  
7" D.Fir, S.41°E., 16.2 ft mkd: "T325 R3W S36 CS BT" (Unrecorded) 36" Cedar, S.4°E. 32.0 ft mkd: "RS 359"  
Note - Corner renewed by Arnold Gibson, Oregon Dept of forestry in 1968 per Baughman 1979 renewal.

Glenn Baughman - For: USFS - Nov. 1979 - C.S. File 58/176-20

-----  
Found - A 1½" iron pipe, firmly set, with a 3" Brass Cap mkd: "OREGON STATE BOARD OF FORESTRY T32S R3W S25 S26 S33 S36 1968" the top of brass cap is set over a 18x12x7" Serpentine Stone with 1 notch on the East and South edges, from which the original bearing trees:  
continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A 48" D.Fir Stump, with scribe marks "S25" visible, bears N.55°E., 35.6 ft.  
A 46" D.Fir Stump, with healed blaze, bears S.15°E., 6.6 ft.  
A 72" D.Fir Stump, with healed blaze, bears N.44°W., 37.6 ft.  
A 60" D.Fir Stump, with scribe marks visible, bears S.35°W., 17.8 ft.  
And BTs marked by Gibson:  
A 40" Cedar, with healed blaze, bears S.4°E. 32.0 ft  
And bearing trees marked by Jones:  
A 20" Pine Stump, with scribe marks "R3W 2 visible, bears N.21°E., 31.5 ft.  
A 20" D.Fir, with scribe marks "R3W" visible on a partially healed blaze, bears S.70°W., 40.2 ft.  
A 8" D.Fir, with healed blaze, bears S.41°E. 16.2 ft  
New - A 8" D.Fir, bears N.32°W., 19.7 ft, mkd. "T32S R3W S26 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.  
A 6" D.Fir, bears N30°E., 10.4 ft, mkd."T32S R3W S25 BT" on a double blaze and nailed a brass washer stamped "LS 536' into lower blaze.

Jackson Co. Surveyors Office, Edward McGinty, Co. Surveyor - R. Frost & H. Durkee, Techs. - 11/1/1988 - C.S. File 63/82-2

Found - OSBF 1968 brass cap on IP projecting 12" (leaning 25° southeast at vertical) Said brass cap is centered over a chiseled cross atop the (firmly set) 10x7x?", original stone, fd. projecting 6".  
Orig. BTs recorded by Mensch in 1913 fd. as follows:  
Burnt fir stump, 48" dia., bears N.55°46'E., 35.64 ft to center. Record; N.55°E.  
Burnt fir stump, 45" dia., bears S.16°41'E., 7.50 ft. to center. Record; S.15°E., 6.60 ft.  
Burnt fir stump, 51" dia., bears S.35°05'W, 18.80 ft. to center. Record; S.35°W., 17.82 ft.  
Burnt fir stump, 66" dia., bears N.44°57'W., 39.45 ft. to center. Record; N.44°W., 37.62 ft.  
A BT mkd. on the above noted survey, a cedar, now a burnt snag, 32" dia., bears S.5°49'E., 31.5 ft. Record; S.8½°E., 31.6 ft.  
The above BTs were also reported by the DCSO on 1969 reestablishment. BTs mkd. by the County Surveyor fd:  
Burnt pine stump, 16" dia., bears N.21°E., 31.3 ft. to center. Record; 31.5 ft.

continued next page

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Burnt fir snag, 7" dia. with healed blaze bears S.41°E., 15.90 ft. to center. Record; 16.2 ft  
Burnt fir stump, 21" dia., bears S.69°39'W., 39.75 ft. to center. Record; S.70°W., 40.2 ft.

A BT not of record (in Jackson County),  
A burnt fir snag, 7" dia., with nail through washer, stamped "CS 536" in lower, burned face, bears N.28°43'E., 1045 ft.

As all trees within a reasonable distance of the corner have been destroyed by recent (1987) forest fire:  
Set - 5/8x24" rebars with yellow plastic caps mkd. "Jackson CS", 23" in the ground, except as noted:  
N.41°59'E., 12.15 ft  
S.38°00'E., 9.05 ft.  
S.73°24'W., 122.45 ft., set 3" deep, 3 ft. South of metal fence post, with attached attention sign, located alongside road, c. N.45°E. - S.45°W.  
N.37°23'W., 9.57 ft.

Corner lies on Southeast slope, an estimated 160 ft. West of draw c. Southeast and 3 ft. West of steel fence post with attention sign.