

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8423)

Set a serpentine stone 18x12x6", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A cedar, 10" dia., bears N.30°E., 19 lks., mkd: ¼ S25 BT.

A cedar, 12" dia., bears N.82°W., 27 lks., mkd: ¼ S26 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Sept. 1969 - C.S. File 54/91-72

Found - 18x12x6 Stone mkd: "¼" on West face, firmly set at corner.

10", now 13" Cedar, N.30°E., 12.5 ft., shows good scar.

12", now 34" Cedar, N.82°W., 17.8 ft., scribe marks visible but mostly grown over.

Set - Brass Cap at Cor. mkd: County Surveyors T32S R3W Office, 1969 ¼ S 26|S 25

All Bearing Trees OK and Tagged.