

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 23 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8424-5)

Point for ¼ sec. cor. falls on exposed serpentine bedrock on which I cut a cross (X) at exact point, for ¼ sec. cor. and mark ¼ W of cross; from which
 A yellow pine, 7" dia., bears S.23°20'E., 42 lks., mkd: ¼ S24 BT.
 A pinon, 12" dia., bears S.24°45'W., 59 lks. mkd: ¼ S23 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1969 - C.S. File 54/91-74

Found - 7", now 17" Yellow Pine, S.23½°E. 27.2 ft., opened for scribe "4"
 No trace of SW BT. or marks at corner on bed rock, due to erosion.
Set - Brass Cap at Cor. mkd County Surveyors T32S R3W Office, 1969 ¼ S23|S24
New BT - 14" Cedar S.32°W. 29.7 ft. mkd: "¼ S23 CS BT".