

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION CC Secs 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8425)

-----

Intersect S. bdy of sec. 13, East 16.19 chs. from the cor. of secs. 13 & 14.  
At point of intersection, I set a slate stone, 15x8x6", 10" in the ground, for closing cor. of secs. 23 & 24, marked CC on S with 1 groove and E face; from which  
    A fir, 28" dia. bears S.55°E., 19 lks mkd: T32S R3W S24 BT  
    A fir, 10" dia. bears S.12°W., 46 lks mkd: T32S R3W S23 BT

J. H. Markham, Jr - For: M & B Logging Co. - Wit: S.J. Pritchett - Nov. 9, 1958 - C.S. File 42/356-19

-----

Found - 36" fir stump, logged, bears S.55°E., 12.5 ft. OBT.  
    I rescribed S24 on top & BT on bark.  
At corner point set truck axle with flange up from which:  
    10" W.Fir bears S.46°E., 68.0 ft. mkd: S24 BT.  
    12" Fir bears S.68°E., 144.0 mkd: S24 BT.  
Road bears East 165.0 ft.

Fd. Ok 8/5/1969 JMP, DCSO - C.S. file 54/91-46