

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 20 Page(s) 8386)

Set an ironstone 12x8x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on West face, from which

A R.Fir, 16" dia., bears N.64°E., 32 lks., mkd: ¼ S13 BT.

A Maple, 8" dia., bears N.26°W., 13 lks., mkd: ¼ S14 BT.

Fd. & used on GLO survey by Fred Mensch, Deputy Surveyor-Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8399)

Douglas Co. Surveyors Office - Frank Jones & W. Penley - 7/22/1969 - C.S. File 54/91-27

Reported as not found

Because the ¼ cor. falls in the fill of a logging road & stumps that are showing are burnt up. We had good line and calls on the ¼ cor.

Don Garrett - For: USFS - 9/7/1971 - C.S. 55/215 & M43-53

Desc. of cor. evidence found: I made tie to cor. from traverse of E. line of Sec. 14. In clear-cut unit, approx. 250 N. of road & S. of small creek, I found a 21" Fir stump. I chopped out old scribing & found ¼ scribed clearly in stump. I found iron stone in approx. location of orig. ¼ corner. Stone had been knocked 2 ft. N. of orig. position by logging operations & was lying on its side. The stone had ¼ clearly marked on its side. 8" Maple BT was destroyed by logging operations.

I reestablished the location of the corner from the stump of the orig. BT., S.64°W. 32 lks. At this location, I set a 2"x30" galv. Iron pipe, flared at the bottom, with a 3" bronze cap welded to the top. I placed the orig. stone monument described above, in hole, alongside iron pipe.

I stamp this cap
T32S R3W
¼ S 14 | S 13
RLS 544
1971

From the pipe monument, the Orig. BT. is:

A 16" Red Fir, now 21 stump, bears N.64°E. 32 lks.

I also established new BT stumps, as follows:

25" Fir Stump bears N.88°W. 54.9 ft. scribed ¼ S24 BT.

40" Fir Stump bears N.23½°E. 73.6 ft. scribed ¼ S13 BT.

A 6' Steel Fencepost with sign 54-4 -attached, bears North 5 ft.