TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 20 Page(s) 8361)

Set ¼ sec. post, from which
A Laurel, 10" dia., bears N.70°E., 27 lks.
A Laurel, 10" dia., bears S.75°W., 9 lks.

GLO survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 20 Page(s) 8391-2)

The ¼ sec. cor. is not fd after careful search. . . .
Re-establish the Sec. cor. as follows:
Set a Fir post, 3 ft. long, 4" sq., 24" in the ground, for Sec cor., marked ¼ S11 on W. face & 12 on E face, from which
A R.Fir 30" dia., bears East, 20 lks., marked ¼ S 12 BT.
A R.Fir, 30" dia., bears S.27°W., 23 lks., mkd: ¼ S11 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1969 - C.S. File 54/91-6

Found - 30" now 38" D.Fir, East 13.2 ft. shows good axe face
30" now 37" D.Fir, S.64°W. (Rec.S.27°W.) 15.2 ft., opened & find scribe.
Set Brass Cap at Cor. Mkd: County Surveyors Office, 1969 T32S R3W ¼ S11|S12
No New Bearing Trees needed.
This corner lies on steep north slope and 300 ft. N. of Callahan Pack Trail.

See C.S. File 63/166, T32S R3W folder, for 2005 correspondence between USFS & the BLM concerning the subdivision of Secs 1 & 12. This files are not available on the internet.