

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor Secs 1, 2, 11, & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCS0 records Vol. 20 Page(s) 8361)

Set post, cor. to secs. 1, 2, 11, & 12, from which
A fir, 24" dia., bears N.12°E., 22 lks.
A fir, 14" dia., bears S.50°E., 47 lks.
A fir, 24" dia., bears S.58°W., 9 lks.
A fir, 16" dia., bears N.30°W., 15 lks.

GL0 survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCS0 records Vol. 20 Pgs 8389 & 8390)

I re-establish the cor. in its orig. position as follows:
Set a ironstone 20x10x5", 15" in the ground for cor. of secs. 1, 2, 11, & 12 mkd with 5 notches on S & 1 notch on E edge, from which from which
A R.Fir, 20" dia., bears N.59°E., 216 lks., mkd: T32S R3W S1 BT.
A R.Fir, 30" dia., bears S.26°E., ~~200~~ 251* lks., mkd: T32S R3W S12 BT.
An Alder, 10" dia., bears S.66°W., 92 lks., mkd: T32S R3W S11 BT.
A R.Fir, 30" dia., bears N.40°W., 387 lks., mkd: T32S R3W S2 BT.
No nearer BT is available in Sec. 2
*Pg 8390 SE BT at this corner reported in my orig description of re-establishment at 200 lks. is fd to be 251 lks

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S.A. Bilow - Feb. 24, 1959 - C.S. file 49/136-2

Found - Orig. 20"x10"x5" stone 15" in the ground & marked as recorded.
Now 48" Fir down & mostly rotted that checks bearing & distance for Original NW BT no scribing found.
No trace of other BTs fd. The SW BT may have been washed out.
The NE & SE BTs would be in field.
Set brass cap alongside corner stone mkd:
COUNTY SURVEYORS OFFICE
1959 S 2 | S 1 T32S R3W
 S 11 | S 12
Note - Corner under N-S fence.
New BTs- 16" Hemlock bears S.2°W., 91.1 ft. scribed S11 T32S R3W CS BT.
 18" R.Fir bears N.86°W., 203.9 ft. scribed S2 T32S R3W CS BT.
continued next page

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor Secs 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" W.Fir bears S.20°E., 263.6 ft. scribed S12 T32S R3W CS BT.
FD. Ok by JMP, DCSO 7/9/1969 - C.S. File 54/91
Malcolm Clark - For: USFS - April 1980 - M83-53 & M83-54 ----- Found - Douglas County Surveyors 1959 brass cap. 18" Hemlock bears S.01°20'W., 91.2 ft. 24" D.Fir bears N.86°35'W., 204.3 ft. New BTs- 12" Knobcone pine bears N.12°40'E., 555.0 ft. scribed "T32S R3W S1 BT" 18" W.Fir bears S.03°35'E., 250.7 ft. scribed "T32S R3W S12 BT". Both new BTs have a 3/4" brass disc stamped "RLS 601" nailed flush with lower blaze.
Stephen Barott - For: Roger Hardage, ET AL - USFS COOP Survey - 3/2007 - M152-65 & C.S. File 65/61-5 A-E ----- Found - 1½" dia. iron pipe with a 3" dia. brass cap monument mkd as shown on plat, protruding 14" above ground. From which the following accessories: 25" dia. Hemlock bears S.01°31'19"E., 91.3 ft. with a healed double blaze. 18" dia. Knobcone Pine fir bears N.12°45'43"E. 549.7 ft, w/fragmentary scribing visible on partially healed blaze [rec 555.0 ft] 42" dia. fir bears N.86°35'19"W., 204.5 ft with a healed double blaze. 27" dia. fir bears S.03°25'26"E., 250.5 ft with a partially healed blaze. GPS Point DF-1 bears N.32°44'06"E., 508.40 ft. Corner lies on a gentle south slope and in a fence line, 500 feet south of Cow Creek Road No. 36. National Forest property boundary marked West and South from corner. Sec. Cor 1, 2, 11, 12 <u>GPS info: Used Trimble R8 GPS Receivers</u> Latitude: 42°48'46.869"N Longitude: 123°00'47.383"W Elevation: 2237.1 ft.
See C.S. File 63/166, T32S R3W folder, for 2005 correspondence between USFS & the BLM concerning the subdivision of Secs 1 & 12. This files are not available on the internet.