TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 624400

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 13 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 20 Page(s) 8387)

Set a serpentine stone 15x8x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A R.Fir, 12" dia., bears N.7°W., 48 lks., mkd: ¼ S13 BT.
A R.Fir, 10" dia., bears S.67°W., 26 lks., mkd: ¼ S24 BT.

GLO survey by Fred Mensch, Deputy Surveyor- Under special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8398-9)

Intersect the ¼ sec. cor. which is a stone, firmly set, marked & witnessed as described by the Surveyor General, and which I now change to refer to sec. 13 only, and witness as follows:
From the corner already set,
A Pinion, 5" dia., bears N.79°E., 37 lks., mkd: ¼ S13 BT.
A fir, 12" dia., bears N.7°W., 48 lks., mkd: ¼ S13 BT.
I destroy the marks on former BT, referring to Sec. 24.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1969 - C.S. File 54/91-45

Found - Corner Stone, 15x8x6 with "¼" on N. side & in place.
Orig.12" D.Fir, now 14" Snag, N.7°W. 31.7 ft., shows good scribing.
Orig. 5" Y.Pine (Record 5" Pinion), now 8", N.79°E. 24.4 ft., shows scribing.
Set - Brass Cap at Cor. mkd: County Surveyors (alongside Corner Stone) Office 1969 T32S R3W ¼ S 13
New BT - 8" Y.Pine N.21°E. 20.2 ft. mkd: "¼ S13 CS BT"
This ¼ corner lies approx. 40.0 ft. west of spur and on south slope.