TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 20 Page(s) 8385)

Set a slate stone 12x10x5", 8" in the ground for ¼ sec. cor. mkd. ¼ on North face, from which
A R.Fir, 10" dia., bears N.52°E., 21 lks., mkd: ¼ S12 BT.
A R.Fir, 6" dia., bears S.50°E., 29 lks., mkd: ¼ S13 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - 7/1969 - C.S. File 54/91-5

Reported as not found.
This cor. is probably logged or possibly in old logging road.
2 sm fir 2-10" trees in this area grow very slow.

Don Garrett - For: USFS - March 24, 1972 - M44-62

Set Brass Cap by prop. meas.: Stamped: T 32 S R 3 W
¼ S 12
S 13
1972
RPLS 544

Established Bearing Trees:
26" D.Fir bears N.2°E. 41.9 ft. scribed "¼ S12 BT".
19" D.Fir bears S.55½°W. 27.8 ft. scribed "¼ S13 BT".

See C.S. File 63/166, T32S R3W folder, for 2005 correspondence between USFS & the BLM concerning the subdivision of Secs 1 & 12. This files are not available on the internet.