

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 642700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only, T31-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7695)

Set a stone 14x10x4 ins., 10" in the ground, for ¼ sec.cor. marked ¼ on N. face; from which

A Laurel 4" dia., bears N.23½°E., 33½ lks. dist. mkd. ¼ S BT.

A Pine 26" dia., bears S.34 3/4°E., 125 lks. dist. mkd. ¼ S BT.

Survey by William Ruppert - For: U.S. Forest Service - June 1980 - C.S. File 58/229

Found - 4" x 10" x 14" stone with "¼" plainly visible on North face.

45" Ponderosa Pine bears S.23°34'E., 83.8 ft. with a good scar.

Set a 2" x 30" alum. pipe into the ground and constructed a mound of stones around it. I marked the attached 2½" alum. cap as "T31S R3W ¼ S36 PLS 866 1980".

New BTs- 26" D.Fir bears N.71°12'E., 29.8 ft. scribed ¼ S36 BT.

26" D.Fir bears N.21°35'E., 11.5 ft. scribed ¼ S36 BT.

A brass washer marked "LS 866" is nailed to each lower blaze.

Fd. OK, March 1991 - M 111-67