

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 674673

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 of T31-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7695)

-----  
Set a Fir post 4 ft. long, 4" sq., 24" in the ground for cor. to tps. 31 and 32 S., Rs. 2 and 3 W., marked T31S S31 on NE.; R2W S6 on SE.; T32S S1 on SW.; R3W S36 on NW. faces, with 6 notches on each edge, from which

A Cedar 8" dia., bears N.40½°E., 101 lks. dist., mkd. T31S R2W S31 BT.

A Fir 10" dia., bears S.14°E., 12 lks. dist. mkd. T32S R2W S6 BT.

A Fir 9" dia., bears S.15 3/4°W., 42 3/4 lks. dist. mkd. T32S R3W S1 BT.

A White Fir 28" dia., bears N.55°W., 87 lks. dist. mkd. T31S R3W S36 BT.

GLO resurvey by Fred Mensch, under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 20 Page(s) 8354 B)

-----  
Intersect the cor. of Tps. 31 S, Rs. 2 and 3 W. I destroy this corner and in its original position, establish cor. for T31S R3W, as follows:

Set a Fir post, 3 ft. long, 5" sq., 24" in the ground for SE. cor. of T31S R3W, marked S1 on NE.; S32S R3W S1 on SE.; S1 on SW. and T31S R3W S36 on NW. face, with 6 notches on N. and W. edges; from which

A W.Fir 30" dia., bears N.55°W., 87 lks. dist. mkd. T31S R3W S36 BT.

No stones obtainable.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: J.R. Markham - Oct. 29, 1958 - C.S. File 42/392-4

-----  
Determined by O.B.T.s:

40" W.Fir bears N.55°W., 60.5 ft.

11" Cedar bears N.40°E., 68.5 ft., I remark "S1 BT".

24" Fir bears S.14°E., 7.9 ft., I remark "S1 BT".

15" W.Fir bears S.16°W., 28.4 ft., I rescribed "S1 T32S R2W BT".

At corner point, Set 3/4" x 60" Iron pipe, 36" in ground.

Road bears North 250.0 ft. dist.

SW. Corner Sec. 31 bears North 441.0 ft.

Douglas Co. Surveyors Office - John M. Powell, & crew - Aug. 30, 1966 - C.S. File 54/28-89

-----  
Found - 3/4" I.Pipe, bent over under small log.  
(Cont. Next Page)

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 674673

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 of T31-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

40" W.Fir N.55°W., 60.5 ft., shows good scar.  
11" now 14" Cedar N.40°E., 68.5 ft., scribe visible  
"S1 BT".  
15" W.Fir, now stump S.16°W., 28.4 ft., opened for  
scribe "T32".  
24" D.Fir, now down, S.14°E., 7.9 ft.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R |  
S 36 | 3W |  
S 1  
T 32 S  
Reblazed and rescribed:  
14" Cedar N.40°E., 68.5 ft. "T32S R3W S1 CS  
BT."  
No other trees available. Cor. lies just on S. side of small  
ridge.

Survey by William Ruppert - For: U.S. Forest Service - May  
1980 - C.S. File 58/143(n) and M 84-4  
-----  
Found - 1" galv. I.P. with 1966 county brass cap.  
15" I.Cedar N.40°20'E., 68.4 ft. "T32S R3W S1 CS BT"  
visible.  
16" rotten stump S.15°56'W., 28.5 ft., two faces,  
one face has chopped scribing visible.  
31" Fir uproot, N.59°24'W., 60.6 ft., hollow face.  
New BT - 13" Yew N.64°24'W., 67.6 ft. scribed "T31S R3W S36  
BT". Attached 3/4" brass washer mkd. "LS 866" to  
lower blaze.

James Klein - Keith Primm - Douglas Popham - For:  
Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I  
-----  
Found - 2½" brass cap (properly mkd) 1966  
25" cedar with healed face & tag dated 6/80  
N.40°20'E., 68.4' to nail side center.  
14.5" yew with visible scribe & tag dated 6/80  
N.64°24'W., 67.6' to nail side center.