

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 678700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 31 only, T31-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7609-10)

Set an ironstone 20x12x6 ins., 15" in the ground for ¼ sec. cor. marked ¼ on the N. face, from which
A Cedar 12" dia., bears n.56½°E., 43 lks. dist. mkd. ¼ S31 BT.
A Fir 12" dia., bears N.55°W., 58 lks. dist. mkd. ¼ S31 BT.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7618) and page 7626)

(Page 7618)
The Qr. Sec. cor. on South Bdy. sec. 31, which is an ironstone 5x10x6 ins., above ground, firmly set, marked and witnessed as described by the surveyor general.

(Page 7626)
(9.63 chs.)
Set a slate stone 18x10x8 ins., 12" in the ground for ¼ sec. cor. marked ¼ on N. face, from which
An Alder 8" dia., bears N.14°E., 93 lks. dist. mkd. ¼ S31 BT.
A Fir 18" dia., bears N.79°W., 52 lks. dist. mkd. ¼ S31 BT (14.10 chs.)
The old ¼ sec. cor. on S. bdy. sec. 31.
I destroy the cor. and marks on bearing trees.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: J.R. Markham - Oct. 29, 1958 - C.S. File 42/392-6

Determined by O.B.T.s:
26" Fir windfall, bears n.79°W., 34.4 ft., found scribe.
22" Alder N.14°E., 61.4 ft.
At corner point, SET 1" x 30" Iron pipe, from which
10" Hemlock bears N.27°W., 8.2 ft. mkd. ¼ S31 BT.
12" Alder bears S.55°W., 3.0 ft. mkd. ¼ S31 BT.
Corner lies in creek. Twp. cor. bears West 575.0 ft. Road bears East 295.0 ft. NW. corner Sec. 6 bears East 366.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Terry Connell, crew - Aug/Sept. 1966 - C.S. File 54/2884

Found - 1" Iron pipe at ¼ corner.
(Cont. Next Page)

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 678700

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 31 only, T31-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" Alder now 15 ft. snag, S.55°W., 3.0 ft., scribe visible "¼S".
10" Hemlock now down, N.27°W., 8.2 ft.
New BTs- 19" W.Fir N.74°E., 104.4 ft. mkd. ¼ S31 CS BT (In old road)
52" Fir stump N.42°W., 73.3 ft. mkd. ¼ S31 CS BT.
Corner lies in creek which runs S.14°W-N.14°E., in cut unit.

Survey by Malcolm Clark - For: U.S. Forest Service - April 1980 - C.S. File 58/227 and M 83-53

Found - 12" x 18" x 8" stone with "¼" clearly chiseled on N. face.
52" Fir stump bears N.40°30'W., 75.3 ft., scribing visible.
19" W.Fir bears N.72°15'E., 111.0 ft., scribing visible.
A 1" Iron pipe bears N.33°W., 4.15 ft.
Set an alum. cap in the position of the stone stamped: "T31S R2W ¼ S31 T32S R3W (?) 1980 RLS 601".
New BT - 6" Madrone bears N.26°15'W., 65.3 ft. scribed "T31S R2W ¼ S31 BT".

James Klein - For: Williams/Pacific Connector Gas Pipeline Project - 4/2015 - M166-35 A-H

Found - 2½" alum. cap stamped RLS 601, 1980
28" W.Fir with healed face, SET tag dated 2/25/2015 N.72°E., - 111.0'
16" Madrone with healed face SET tag dated 2/25/2015 N.26°15'W., 65.3'
52" dia. stump with visible scribes with tag dated 1/80 N.40°30'W., - 75.3'
New BT - 24" D.Fir (mkd - SC¼ S31 BT) SET tag dated 2/15 N.21°E., - 29.0' to nail side center
12" D.Fir (mkd - ¼ S1 BT) SET tag dated 2/15 S.36°E., - 16.7' to nail side center