

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, U.S. Surveyor, Under Special instructions dated Aug. 20, 1912 - (DCSO records Vol. 20 Page(s) 8356)

Set a granite stone 15x12x6 ins., 10" in ground for cor. of secs. 24 and 25 only, marked with 2 notches on S. and 4 notches on N. edge, from which
A Sugar Pine 12" dia., bears S.82°W., 25 lks. dist. mkd. T32S R3W S25 BT.
A Fir 12" dia., bears N.60°W., 45 lks. dist. mkd. T32S R3W S24 BT.

Glenn S. Baughman - For: U.S. Forest Service - Aug. 1968 - C.S. File 55/87-17

Found - Stone 15"x12"x6" with 2 notches on S. and 4 notches on N. edges.
Orig. 12" now 24" Fir bears N.60°W., 29.7 ft. mkd. T32S R3W S24 BT.
Orig. 12" now 24" S.Pine with closed face, bears S.82°W., 16.5 ft.

Set 2" x 30" I.P. with brass cap stamped;
T 32 S
R3W -cc S 24 | S30 R2W
S 25 |
1968
OLS 536

From the pipe monument, the orig. BTs are;
24" Fir bears N.60°W., 29.7 ft. mkd. T32S R3W S24 BT
24" S.Pine bears S.82°W., 16.5 ft. remarked T32S R3W S25 CC BT.

Placed BT tags on all BTs and facing the monument.
(Note: Letter from BLM and filed in this CS File, states that they would not call this corner a closing corner.)