

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 700432

PRIMARY CORNER DESCRIPTION W. 1/4 cor. for Sec. 18 only, T32-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5, 1902 - (DCSO records Vol. 19 Page(s) 8289)

Marked a Fir 14" dia. for 1/4 sec. cor., marked 1/4 S13 on W. and S18 on E. faces, from which
A Fir 18" dia., bears S.54°E., 20 lks. dist. mkd. 1/4 S BT.
A Fir 24" dia., bears S.20 1/2°W., 30 lks. dist. mkd. 1/4 S BT

Tied Cor. in BLM survey by Fred Mensch, Sept. 14, 1904 - DCSO records, Vol. 20 Page 8353

Survey by Glenn S. Baughman - For: U.S. Forest Service - Aug. 1968 - C.S. File 55/87-3

Found - Orig. 24" now 38" Fir S.20°W., 19.8 ft., opened face and found "1/4 S18 BT" in good condition.
Set 2" x 30" I.P. with brass cap stamped: T 32 S
R3W 1/4 R2W
| S 18
1968
OLS 536

From the pipe monument, the orig. BT is:
38" Fir bears S.20°W., 19.8 ft. mkd. 1/4 S18 BT.
New BT - 40" Fir bears S.27°E., 34.3 ft. mkd. 1/4 S18 BT.
Placed BT tags on all bearing trees and facing the monument.